



# FORMULA SHELL<sup>®</sup> ATF/ SHELL DONAX<sup>®</sup> T FLUIDS

## Premium fluids for automatic transmissions

---

### Product Description

FormulaShell<sup>®</sup> ATF MERCON<sup>®</sup>/DEXRON<sup>®</sup>-III - Donax<sup>®</sup> TG and FormulaShell<sup>®</sup> ATF Type F- Donax<sup>®</sup> TF are formulated to meet the viscometric, friction, wear and oxidation stability properties required in passenger car and light truck transmissions. They are available as DONAX<sup>®</sup> TG and TF in non-retail packages.

### FormulaShell<sup>®</sup> ATF Mercon<sup>®</sup> /Dexron<sup>®</sup> -III- Donax<sup>®</sup> TG

#### Applications

- multipurpose product for use in GM and Ford automatic transmissions except for those that specify Type F or MERCON V.
- recommended for use in Allison automatic transmissions and Caterpillar transmissions that call for TO-2 performance.
- suitable for use in many automatic transmissions made by Voith, Daimler Benz and ZF.
- application as the operating fluid in hydraulic equipment (especially at low ambient temperatures), air compressors, and power steering systems

#### Approvals

- Ford MERCON
- GM DEXRON-III
- GM DEXRON, DEXRON-II, DEXRON-III, Type A and Type A Suffix A
- (GM Transmissions only)
- Allison C-4
- Caterpillar TO-2
- application as the operating fluid in hydraulic equipment (especially at low ambient temperatures), air compressors, and power steering systems

### DONAX TF\FormulaShell ATF TYPE F

#### Applications

- **FormulaShell ATF TYPE F** is recommended for use in all 1976 and prior Ford automatic transmissions as well as many 1977 through 1980 Ford models that specify Type F.
- application as the operating fluid in hydraulic equipment (especially at low ambient temperatures), air compressors, and power steering systems

#### OEM and Industry Approvals

- Ford specification M2C33-F
- application as the operating fluid in hydraulic equipment (especially at low ambient temperatures), air compressors, and power steering systems

**Typical Properties of Shell DONAX TF and TG Oils**

	Test Method	FormulaShell ATF MERCON/DEXRON-III	FormulaShell ATF TYPE F
Product Code		53010	53026
Commerical Package		DONAX TG	DONAX T
Viscosity:			
@ -40°F, cP	D 2983	16300	35750
@ 0°F, cP	D 2983	1030	1460
@ 100°C, cSt	D 445	8.03	7.9
Gravity, °API @ 60°F	D 1298	31.2	30.4
Pour Point, °F	D 97	-45	-55
Flash Point, °F	D 92	405	415
Color	D 1500	Red	Red

**HANDLING & SAFETY INFORMATION**

For information on the safe handling and use of this product, refer to its Material Safety Data Sheet at <http://www.equivashellmsds.com>. For more information and availability, call **1+800-782-7852** or visit the World Wide Web: <http://www.shell-lubricants.com/>.

